

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7495)

-----  
Set a basalt stone 18x10x6 ins., 14" in the ground for cor. of secs. 24 and 25, mkd. with 4 notches on N. and 2 notches on S. face, from which  
A Fir 30" dia., bears S.75°W., 34 lks. dist. mkd. T31s R1W S25 BT.  
A Fir 12" dia., bears N.50°W., 48 lks. dist. mkd. T31S R1W S24 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7508)

-----  
The cor. of secs. 24 and 25 only, which is a basalt stone, firmly set, 4x10x6 ins. above ground marked with 4 notches on N., and 2 notches on S. edge; from which  
A Fir 30" dia., bears S.75°W., 34 lks. dist. mkd. T31S R1W S25 BT. (Old BT)  
A Fir 12" dia., bears N.50°W., 48 lks. dist. mkd. T31S R1W S24 BT. (Old BT)  
Re-mark the stone S25 on SW., and S24 on NW. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-125

-----  
Found - Stone at corner, no marks found.  
30" D.Fir now 6 ft. stob, S.75°W., 22.4 ft., scribe visible.  
12" now 15" D.Fir N.48°W., (Rec. N.50°W.) 31.7 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
1 S 24 | S19 1  
W S 25 | E  
1968

New BTs- 9" D.Fir S.67°W., 36.6 ft. scribed T31S R1W S25 CSBT  
11" R.Fir S.15°E., 17.3 ft. scribed T31S R1E S19 CS BT.