

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700309

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7509)

Set an Iron post 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor. of sec. 19 only, with brass cap mkd. 1/4 S19

1923

from which

A Fir 30" dia., bears N.51°E., 24 lks. dist. mkd. 1/4 S19 BT

A Fir 25" dia., bears S.46°E., 31 lks. dist. mkd. 1/4 S19 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-124

Found - GLO brass cap at 1/4 cor., properly mkd. in 1923
25" D.Fir now 27", S.26°E., (Rec. S.46°E.) 20.5 ft., shows good scar.

30" D.Fir now down, N.51°E., 15.8 ft.

New BT - 14" D.Fir S.60°E., 39.4 ft. scribed "1/4 S19 CS BT"