

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7496)

Set a basalt stone 12x10x6 ins., 8" in ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Fir 10" dia., bears N.25°E., 26 lks. dist. mkd. ¼ S19 BT.

A Fir 40" dia., bears West, 50 lks. dist. mkd. ¼ S24 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7509)

The ¼ sec. cor. established for secs. 19 and 24, which is a basalt stone, firmly sset, 4x10x6 ins. above ground mkd. ¼ on W. face; from which

A Fir 10" dia., bears N.25°E., 26 lks. dist. mkd. ¼ S19 BT. (Old BT)

The old bearing tree in sec. 24 is dead and fallen. I now change this cor. to refer to sec. 24 only, and obliterate the marks on the bearing tree referring to sec. 19. Re-mark the stone ¼ S24 on W. face, from which

A Fir 30" dia., bears S.69°W., 73 lks. dist. mkd. ¼ S24 BT. (New BT)

A Fir 6" dia., bears N.82°W., 23 lks. dist. mkd. ¼ S24 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-129

Found - No trace of corner stone.

30" D.Fir now stump, S.69°W., 48.2 ft., opened for scribe.

6" now 13" R.Fir N.82°W., 15.2 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 31 S	R
1	¼ S24	1
W	1968	E

New BT - 30" D.Fir S.71½°E., 33.6 ft. scribed S19 CS BT.

No trees to the West.