

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700349

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T31-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7509-10)

-----  
Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 18 & 19, only with brass cap marked:

T31S	T31S
R1W	S 18
	S 19
S24	R1E
	1923

from which

A Hemlock 12" dia., bears N.21°E., 65 lks. dist. mkd. T31S R1E S18 BT.

A Fir 26" dia., bears S.43°E., 49 lks. dist. mkd. T31S R1E S19 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-131

-----  
Found - GLO brass cap at cor., properly mkd. in 1922.  
12" Hemlock now burnt stob, N.21°E., 42.9 ft.  
26" D.Fir now burnt stump S.43°E., 32.3 ft. shows good scar.

No trees in area. Tagged all stumps.

New Bearing Stumps:

28" Hemlock stump, N.71°E., 53.6 ft., scribed T31S R1E S18 CS BT.

55" D.Fir stump S.60°W., 45.9 ft. scribed S24 CS BT

Cor. lies in clear cut unit in bottom of draw under burnt-out 5 ft. log on East edge. North of rocky point about 200 ft.