

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7497)

-----

Set a basalt stone 12x8x8 ins., 8" in the ground for cor. of secs. 13 and 24 mkd. with 3 notches on N. and S. edges, from which

A Fir 30" dia., bears S.74°W., 63 lks. dist. mkd. T31S R1W S24 BT.

A Fir 30" dia., bears N.70°W., 15 lks. dist. mkd. T31S R1W S13 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7510)

-----

The cor. of secs. 13 & 24 only, which is a basalt stone, firmly set, 4x8x8 ins. above ground, marked with 3 notches on N. and S. edges, from which

A Fir 30" dia., bears S.74°W., 63 lks. dist. mkd. T31S R1W S24 BT. (Old BT)

The old bearing tree in sec. 13 is dead and fallen. Re-mark the stone S24 on SW.; and S13 on NW. face; from which

A Fir 30" dia., bears N.77°W., 29 lks. dist. mkd. T31S R1W S13 BT. (New BT)

Not found. DCSO in 1968, C.S. File 54/71-130