

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700409

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 18 only, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7511)

Set an Iron post 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor. of sec. 18 only, with brass cap mkd: 1/4 S 18

1923

from which

A Hemlock 5" dia., bears N.43°E., 18 lks. dist. mkd. 1/4 S18 BT.

A Chinquapin 5" dia., bears S.71°E., 37 lks. dist. mkd. 1/4 S18 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-134

Found - GLO brass cap, properly mkd. in 1922.

5" Hemlock now down, N.43°E., 17.9 ft.

5" now 8" Chinquapin S.51°E., (Rec. S.71°E.) 24.4 ft. scribing visible on rotten face.

New BTs- 6" Hemlock N.39°E., 10.0 ft. scribed 1/4 S18 CS BT.

5" Maple S.72°E., 13.8 ft. scribed 1/4 S18 CS BT.

Cor. lies on tip of ridge running about S.72°E and 42 ft. South of creek.