

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7498)

-----

Set a basalt stone 15x10x5 ins. 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Cedar 14" dia., bears S.70°E., 23 lks. dist. mkd. ¼ S18 BT.

A Fir 40" dia., bears N.52°W., 57 lks. dist. mkd. ¼ S13 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7511)

-----

The ¼ sec. cor. established for secs. 13 and 18, which is a basalt stone firmly set, 5x10x5 ins. above ground, marked ¼ on W. face, from which

A Cedar 14" dia., bears S.70°E., 23 lks. dist. mkd. ¼ S18 BT. (Old BT)

The old bearing tree in sec. 13 is dead. I now change this cor. to refer to sec. 13 only, and obliterate the marks on the bearing tree referring to sec. 18. Re-mark the stone ¼ S13 on W. face; from which

A Fir 40" dia., bears S.22°W., 169 lks. dist. mkd. ¼ S13 BT. (New BT)

A Fir 48" dia., bears N.2°W., 177 lks. dist. mkd. ¼ S13 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-137

-----

Found - 5x10x5 stone at ¼ cor., marked "¼" on W. face.

48" D.Fir, now snag, N.2°W., 116.8 ft., shows good scar.

40" D.Fir, now snag, S.22°W., 111.5 ft., shows good scar.

Remains of Cedar S.70°E., 15.2 ft. which was destroyed.

Set Brass cap at cor. mkd:

County Surveyors Office
R      T 31 S      R
1      S 13      1
W      ¼      E
1968

New BTs- 9" D.Fir N.1°W., 13.9 ft. mkd. ¼ S13 CS BT.

8" D.Fir S.83°W., 9.7 ft. mkd. ¼ S13 CS BT.