

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700449

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7512)

Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 7 and 18 only, with brass cap marked:

T31S	T31S
R1W	<u>S 7</u>
S13	S 18
	R1E
	1923

from which

A Fir 40" dia., bears N.53°E., 11 lks. dist. mkd. T31S R1E S7 BT.

A Fir 40" dia., bears S.66°E., 84 lks. dist. mkd. T31S R1E S18 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-138

Found - GLO brass cap, properly mkd. in 1923.
40" D.Fir, now snag, S.66°E., 55.4 ft., shows good scar.

40" D.Fir, now down, n.53°E., 7.3 ft.

New BTs- 10" D.Fir N.66°E., 28.5 ft. scribed T31S R1E S7 CS BT.

6" D.Fir S.45°E., 20.9 ft. scribed T31S R1E S18 CS BT.

13" D.Fir N.41°W., 40.4 ft. scribed T31S R1W S13 CS BT.