

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7498)

-----  
 Set a basalt stone 10x15x6 ins. 15" in the ground for cor. of secs. 12 and 13, mkd. with two notches on N. and 4 notches on S. edges, from which  
     A Fir 18" dia., bears S.55°W., 11 lks. dist. mkd. T31S R1W S13 BT.  
     A Fir 12" dia., bears N.71°W., 21 lks. dist. mkd. T31S R1W S12 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7512)

-----  
 The cor. of secs. 12 and 13 only, which is a basalt stone firmly set, 5x15x6 ins. above ground marked with 2 notches on N. and 4 notches on S. edge; from which  
     A Fir 12" dia., bears N.71°W., 21 lks. dist. mkd. T31S R1W S12 BT. (Old BT)  
 The old bearing tree in sec. 13 is dead and fallen. Re-mark stone S13 on SW.; and S12 on NW. face, from which  
     A Cedar 18" dia., bears S.30°W., 37 lks. dist. mkd. T31S R1W S13 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-136

-----  
 Found - Stone at cor. mkd. with 4 notches.  
         12" now 16" D.Fir N.71°W., 13.9 ft., shows good scar.  
         18" now 24" Cedar, S.30°W., 24.4 ft., shows scar.  
 Set Brass cap at cor. mkd:           County Surveyors Office  
   R       T 31 S       R  
   1       S 12       |       S7   1  
   W       S 13       |       E  
   1968  
 Reblazed and rescribed:  
         16" D.Fir N.71°W., 13.9 ft. "T31S R1W S12 CS BT"  
         24" Cedar S.30°W., 24.4 ft. "T31S R1W S13 CS BT"  
 New BT - 14" Cedar N.6°E., 12.8 ft. scribed T31S R1E S7 CS BT