

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700509

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T31-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7513)

-----  
Set a basalt stone 20x15x8 ins., 15" in the ground for ¼ sec. cor. of sec. 7 only, mkd. ¼ S7 on E. face, from which  
A Fir 28" dia., bears N.23°E., 65 lks. dist. mkd. ¼ S7 BT  
A Fir 36" dia., bears S.26°E., 43 lks. dist. mkd. ¼ S7 BT  
No iron post available.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-135

-----  
Found - Stone at ¼ corner marked "¼"  
28" now 36" D.Fir N.23°E., 42.9 ft., shows good scar.  
36" now 37" D.Fir S.26°E., 28.4 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
1 | S 7 1  
W | ¼ E  
1968

All bearing trees OK and tagged.