

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7499)

-----  
Set a basalt stone 15x12x5 ins., 10" in the ground for ¼ sec. cor., mkd. with ¼ on W. face, from which  
A Fir 10" dia., bears N.60°E., 39 lks. dist. mkd. ¼ S7 BT  
A Fir 12" dia., bears N.84°W., 62 lks. dist. mkd. ¼ S12 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7513)

-----  
The ¼ sec. cor. established for secs. 7 and 12, which is a basalt stone, firmly set, 5x12x5 ins. above ground, mkd. ¼ on W. face; from which  
A Fir 10" dia., bears N.60°E., 39 lks. dist. mkd. ¼ S7 BT. (Old BT)  
A Fir 12" dia., bears N.84°W., 62 lks. dist. mkd. ¼ S12 BT. (Old BT)  
I now change this cor. to refer to sec. 12 only, and obliterate the marks on the bearing tree referring to sec. 7. Re-mark the stone, ¼ S12 on W. face, from which  
A Maple 14" dia., bears S.16°W., 56 lks. dist. mkd. ¼ S12 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-76

-----  
Found - 14" now 14" Maple, S.16°W., 37.0 ft., scribe visible.  
12" now 28" D.Fir, N.84°W., 40.9 ft., shows scar.  
Stone at ¼ corner marked "¼S".  
Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
1 S 12 | 1  
W ¼ | E  
1968

All bearing trees OK and tagged.