

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700549

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T31-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7513-14)

-----  
Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 6 & 7 only, with brass cap marked:

T31S		T31S
R1W		S 6
		S 7
S12		R1E
		1923

from which

A Fir 8" dia., bears N.51°E., 35 lks. dist. mkd. T31S R1E S6 BT.

A Fir 24" dia., bears S.35°E., 55 lks. dist. mkd. T31S R1E S7 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71-74

-----  
Found - GLO brass cap at cor., properly marked in 1923.  
24" now 27" D.Fir, S.35°E., 36.3 ft., shows good scar.

9" now 9" D.Fir N.51°E., 23.1 ft., shows good scar.  
New BT - 24" Cedar N.85°W., 30.5 ft. scribed T31S R1W S12 CS BT.

All other BTs tagged.