

PRIMARY CORNER DESCRIPTION Cor. Secs. 6 & 7 only, West

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11164)

Set a stone 14x10x8", 9" in the ground for cor. of secs. 1, 12, 6, & 7 mkd with 1 notch on N & 5 notches on S edges, from which

- A W.Fir, 16" dia., bears S.59°E., 49 lks., mkd: T31S R2E S7 BT.
- A W.Fir, 36" dia., bears S.23°W., 41 lks., mkd: T31S R1E S12 BT.
- A W.Fir, 36" dia., bears N.46°E., 190 lks., mkd: T31S R2E S6 BT.
- A W.Fir, 40" dia., bears N.75°W., 138 lks., mkd: T31S R1E S1 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept./Nov. 1936 - (DCSO Vol. 46 Page(s) 17627)

The old cor. of secs. 1, 6, 7, & 12, which is a porphyry stone, 18x12x9", firmly set.

I change this cor. to refer to secs. 6 & 7 only

At point for cor.,

Set an iron post, 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 6 & 7, with brass cap mkd:

```

T31S|T31S
R1E |S 6
      |S 7
S 1|R2E
      1936

```

from which

- A W.Fir, 50" dia., bears N.46°E., 188 lks., blaze healed; I do not open. I reblaze & remark this tree T31S R2E S6 BT. (Old BT)
- A W.Fir, 22" dia., bears S.59°E., 49 lks., scribe marks S7 recently uncovered. (Old BT)
- A W.Fir, 50" dia., bears S.23°W., 41 lks., mkd. T31S R1E S12 BT. I obliterate the marks. (Old BT)
- A W.Fir, 42" dia., bears S.35°E., 76 lks., mkd. T31S R2E S7 BT. (New BT)