

TOWNSHIP 31 RANGE 02E POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11318)

Set a stone 10x8x7", 7" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A W.Fir, 12" dia., bears N.10°W., 12 lks., mkd: ¼ S BT.
A R.Fir, 48" dia., bears S.55°W., 45 lks., mkd: ¼ S BT.

Jackson Co. Surveyors Office - B. Malotte and R Frost - June 1978 (added 3/19/2012) - C.S. File 65/76-31

Found - Firmly set, the original 15x10x6" stone; record; 10x8x7" mkd. "¼" on North face.
from which, the single remaining original BT recorded by P. Applegate in 1891,

A D.Fir (record: R.Fir) now 58" dia., with healed blazes, brs. record; S.55°W., 29.70 ft. to estimated lower face. Re-measured: 31.70 ft. to center of tree.

New - I replace said stone with a 1x36" G.I. pipe, set 28" in the ground with a 2½" bronze disc mkd:

JACKSON COUNTY 1978

T31S R2E

¼S $\frac{6}{7}$

I deposit orig. stone alongside corner & mark new tree CS BT Cedar, 33" dia., brs. N.28½°E., 28.5 ft. to center of lower blaze.

Corner lies about 40 ft. South of road, same road brs. West approximately 55 ft.

Dec. 20½°

On Douglas-Jackson Co. Line - check w/Jackson Co. For additional corner renewals.