

TOWNSHIP 31 RANGE 02E POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11317-8)

Set a stone 16x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A larch, 24" dia., bears N.8°W., 8 lks., mkd: ¼ S BT.
A larch, 10" dia., bears S.21°E., 56 lks., mkd: ¼ S BT.

Jackson Co. Surveyors Office - B. Malotte and R Frost - June 1978 - C.S. File 58/183-15

Found - Firmly set, the orig 17x11x9" stone, (Record 16x10x8" mkd "¼" on North face as recorded by S. Truax (our records show Applegate) in 1891. Rotted Fir stump remains found at record location of orig. NW BT.
Set - I replace said stone with a 1"x36" G.I. Pipe, set 30" in the ground with a 2½" bronze disc marked:
Jackson County 1978
T31S R2E
¼ $\frac{5}{8}$
I deposit original stone alongside corner as a memorial.
New BTs- 10" W.Fir dia., bears S.84½°W., 11.80 ft.
13" Shasta R.Fir dia., bears N.4°W., 17.60 ft.
Trees marked CS BT and measurements are to center of trees at lower blaze.
Dec. 21°

On Douglas-Jackson Co. Line - check w/Jackson Co. For additional corner renewals.