

TOWNSHIP 31 RANGE 02E POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5 only, North;

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11134)

Set a stone 12x8x8", 8" in the ground for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ on North face, from which

- A cedar, 24" dia., bears S.30°E., 32 lks., mkd: $\frac{1}{4}$ S BT.
- A W.Fir, 18" dia., bears N.47°E., 51 lks., mkd: $\frac{1}{4}$ S BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21850)

The orig. $\frac{1}{4}$ sec. cor. of secs. 5 & 32, which is a basalt stone, 14x10x8", firmly set, mkd. with cross (X) on top.

I now change this cor. to refer to sec. 5 only.

At point for corner.

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with the orig. stone deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 5 only, with brass cap mkd.

$\frac{1}{4}$ S 5
1937

from which

- A W.Fir, 27" dia., bears N.44°E., 49 lks., mkd: $\frac{1}{4}$ S BT. I obliterate the marks on this trees (Old BT)
- A cedar, 30" dia., bears S.36°E., 32 lks., blaze healed. I do not open (Old BT)
- A W.Fir, 8" dia., bears S.29°W., 20 lks., mkd. $\frac{1}{4}$ S5 BT (New BT)

(S.89°01'E., 1.96 chains to South $\frac{1}{4}$ corner Sec. 32)