

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch , U.S. Deputy Surveyor - under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 20 Page(s) 8354 A)

(Intersect E. bdy. of T31S R3W, 6.82 chs. North of the cor. of Tps. 31S Rs. 2 and 3W.)

Set a Fir post 3 ft. long, 5" sq., 24" in the ground for cor. of Tp. 31 S, R2W. and Tp 32 S, R3W, on E. bdy. of Tp. 31 S., R3W, marked T31S R2W S31 on NE.; and T32S R3W S1 on SE. face, with 6 notches on N. & E. edges; from which

A Red Fir 24" dia., bears N.42°E., 36 lks. dist. mkd. T31S R2W S31 BT.

A Red Fir 18" dia., bears S.43°E., 42 lks. dist. mkd. T32S R3W S1 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7618)

The closing cor. of Tps. 31 S., R. 2 W., and 32 S R 3 W on the East bdy. of T31-3, established by me under Contract #757, which is a Fir post 4" sq., 12" above ground, firmly set and marked T31S R2W S31 on N.; C C on E., and T32S R3W., S1 on S.; with 6 grooves on N. and E. faces, from which

A Fir 24" dia., bears N.42°E., 36 lks. dist. mkd. T31S R2W S31 BT.

A Fir 18" dia., bears S.43°E., 42 lks. dist. mkd. T32S R3W S1 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - Oct. 29, 1958 - C.S. File 42/392-7

Determined by O.B.Ts:

36" Fir bears N.43°E., 23.0 ft.

24" Fir stump, logged, bears S.43°E., 23.8 ft.

At corner point, Set 1" x 30" Iron pipe, from which

8" Hemlock bears S.44°E., 28.0 ft. mkd. S1 T32S BT.

13" W.Fir bears N.49°E., 45.0 ft. mkd. S31 T31S R2W BT.

16" Fir bears S.6°30'E., 15.4 ft. mkd. S1 T32S R2W BT.

Road bears East 75.0 ft.

SE. Corner Sec. 36, T31-3, bears South 441.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & T. Connell, crew - Aug. 1966 - C.S. File 54/28-111

Found - 1" I.P. at corner. I.P. in good condition.

Orig. 36" D.Fir now 40", N.43°E., 23.0 ft.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" Hemlock, tree dead, S.44°E., 28.0 ft. scribe visible "S1 T32S".
16" D.Fir now snag, S.6½°E., 15.4 ft., scribe visible.
13" now 15" W.Fir N.49°E., 45.0 ft., scribe visible.
New BT - 27" D.Fir S.32½°E., 34.7 ft. scribed T32S R2W S1 CS BT.
Road bears East 75.0 ft., however, it lies in an old unit and grown over with small alder. Best way to reach corner is by walking down some from main road.

Survey by William Ruppert - For: U.S. Forest Service - May 1980 - M 84-4 and C.S. File 58/143(n)

Found - 1½" Iron pipe.
36" D.Fir N.41°26'E., 23.1 ft., good scars.
14" W.Fir N.47°42'E., 44.5 ft., scribing partly visible.
10" Hemlock snag, S.42°50'E., 27.5 ft.
31" D.Fir S.31°30'E., 34.3 ft. bark scribe "7 1/8" good scar.
18" D.Fir snag S.4°50'E., 15.3 ft. "S1 T32S R2W BT" visible.
Set 2" x 30" Galv. Iron pipe with 2½" brass cap mkd. "PLS 866 T31S S36 R3W T31S R2W S31 CC S1 T32S R3W 1980".

James Klein & Michael Erickson - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-25 A-H

Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1966
38" D.Fir snag with healed face and tag dated 6/80; N.42°E., 22.8' to nail side center
41" D.Fir with healed face and tag dated 6/80; S.29°E., 34.0'
20" Hemlock with healed face and tag dated 6/80; N.50°E., 44.6' to nail side center
New - 11" D.Fir set tag dated 8/14; N.20°W., 14.3' to nail side center