

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100133

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only, T31-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7696)

-----  
Set a stone 14x12x10 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on N. face; from which

A Sugar Pine 30" dia., bears S.76¼°E., 30 lks. dist. mkd. ¼ S BT.

A Sugar Pine 20" dia., bears N.46¼°W., 41 lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7624-25)

-----  
Found a granite stone 5x12x10 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general. I reestablish this cor. in its original position for sec. 36, T31S R3W., only, as follows:

A Granite stone 5x12x10 ins. above ground already set for ¼ sec. cor. on East bdy. Sec. 36, mkd. ¼ on W. face, from which

A Sugar Pine 20" dia., bears N.46°W., 41 lks. dist. mkd. ¼ S36 BT.

A Sugar Pine 28" dia., bears S.75°W., 31 lks. dist. mkd. ¼ S36 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Allen Kusler - July 29, 1955 - C.S. File 42/23

-----  
Determined from O.B.T.s:

22" S.Pine windfall, bears N.76°W., 20.5 ft., found scribe

33" yellow Pine bears S.46°E., 27.0 ft., found scribe.

At corner point, Set a 1" x 30" Iron pipe and large pile of stones, from which

An 18" Cedar bears S.19°W., 48.5 ft. mkd. ¼ S36 BT.

West ¼ cor. Sec. 31, T31S R2W., bears North 435.0 ft.

Centerline of logging road bears West, 72.0 ft.

Searched for not found, DCSO, John Powell, Aug. 1966 C.S. File 54/28-109A

Survey by William Ruppert - For: U.S. Forest Service - May 1980 - C.S. File 58/143(n) and M 84-4

-----  
WITNESS CORNER

Set 2" x 36" galv. I.P. with brass cap mkd. "T31S WC 1/4 R3W S36 N.0°14'E. 122.79 ft. R2W PLS 866 1980". Constructed mound of rocks around pipe.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100133

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only, T31-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

New BTs- 11" D.Fir S.25°29'W., 62.8 ft.  
13" D.Fir S.41°05'W., 54.6 ft.  
Both trees scribed "WC 1/4 S36 BT"  
¼ Corner bears N.0°14'E., 122.79 ft. from witness corner.

Fd. OK, March 1991 - M 111-67

James Klein - Keith Primm - Douglas Popham - For:  
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I  
-----  
Found - 2½" brass cap stamped N.0°14'E., 122.79, PLS 866,  
1980  
19.5" fir with healed face & tag dated 6/80  
S.25°29'W., 62.8' to nail side center.  
16.5" fir with healed face & tag dated 6/80  
S.41°05'W., 54.6' to nail side center.

Douglas Co. Surveyors Office - Crew: Stephen J Flauser & Jeff  
Lorsung - 10/28/2020 - C.S. File 67/46-47  
-----

Fd OK  
Very south edge rock pit grnd.  
Lat: 42.834620868 Long: -122.993227929