

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7637)

Set a slate stone 18x9x6 ins., 12" in the ground for closing cor. of secs. 30 and 31 marked C C on E. with 5 grooves on N. and 1 groove on S. face, from which

A Fir 36" dia., bears N.40°E., 17 lks. dist. mkd. T31S R2W S30 BT.

A Fir 12" dia., bears S.48°E., 36 lks. dist. mkd. T31S R2W S31 BT.

Destroy marks on bearing trees at former cor. referring to secs. 30 and 31.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 52/63-98

Found - Stone at sec. cor. mkd. CC on East face.

36" D.Fir now 40", N.40°E., 11.2 ft., shows good scar.

12" D.Fir now snag, S.48°E., 23.8 ft. opened for scribing. (This brg. should be S.40°E.)

Set Brass cap at cor. mkd: County Surveyors Office

R	T 31 S	R
3	S 30	2
W	S 31	W
	1966	

New BT - 24" D.Fir S.10°W., 34.0 ft. scribed T31S R3W S25 CS BT.