

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7652-53)

-----

Set a granite stone 15x10x6 ins., 10" in the ground for closing cor. of secs. 19 and 30, marked CC on E. with 4 grooves on N. and 2 grooves on S. face, from which

A Fir 20" dia., bears N.26°E., 6 lks. dist. mkd. T31S R2W S19 BT.

A Cedar 20" dia., bears S.10°E., 25 lks. dist. mkd. T31S R2W S30 BT.

Destroy marks on bearing trees at former cor. referring to secs. 19 and 30.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-33

-----

Found - 20" Fir now 23" N.26°E., 4.0 ft., shows good scar.  
20" now 24" Cedar S.10°E., 16.5 ft., This tree opened and some scribing visible "S30".

Set Brass cap at cor. mkd: County Surveyors Office 1965

T31S S 24 |  $\frac{S 19}{S 30}$  R2W  
R3W

Trees in good shape, no need for new BTs.