

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7657)

No stones obtainable.
Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 18 & 19 marked S18 on N.; CC T31S R2W on E.; and S19 on S. face, with 3 grooves on N. and S. faces, from which
A Fir 24" dia., bears N.70°E., 11 lks. dist. mkd. T31S R2W S18 BT.
A Fir 24" dia., bears S.31°E., 20 lks. dist. mkd. T31S R2W S19 BT.

Douglas Co. Surveyors Office - John M. Powell, & crew - Jan. 28, 1966 - C.S. File 52/63-73

Found - 24" now 30" Fir N.70°E., 7.3 ft., shows good scar.
24" now 30" Fir S.31°E., 13.2 ft. shows good scar
Squared stake at C. corner, N. face scribed S18, 3 notches.

Set Brass cap at cor. mkd: County Surveyors Office
R T 31 S R
3 S 24 | S 18 2
W S 24 | S 19 W
1966

Both bearing trees in good condition.