

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCS0 records Vol. 18 Page(s) 7661)

Set a slate stone 18x8x4 ins., 12" in the ground for closing cor. of secs. 7 and 18 marked CC on E. with 2 grooves on N. and 4 grooves on S. face, from which

A Fir 36" dia., bears N.68°E., 65 lks. dist. mkd. T31S R2W S7 BT.

A Cedar 24" dia., bears S.45°E., 5 lks. dist. mkd. T31S R2W S18 BT.

Destroy marks on bearing trees at former cor. referring to secs. 7 and 18.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd & O.A. Keatley - Nov. 23, 1959 - C.S. File 42/392-44

Determined by O.B.T.s:

35" Cedar bears S.45°E., 3.3 ft. I rescribe "S18 R2W BT"

42" Fir N.68°E., 42.8 ft.

At corner point, SET 1/2" x 30" Iron pipe, from which

4" Fir N.80°E., 19.0 ft. "S7 R2W BT"

12" Fir S.11°W., 14.8 ft. "S12 R3W BT"

10" Fir S.87°W., 12.4 ft. "S12 R3W BT"

SE. corner S. 12 bears South 118.0 ft.

Survey by Loyd R. Moffit LS #944 - For: Umpqua National Forest - Aug. 1978 - M 72-76

Found 3/4" Pipe with orig. corner stone.

Set 2" Pipe with 3" brass cap stamped "T31S R3W S12 T31S S7 S18 CC R2W PLS 944 1978"., from which

A 42" Fir bears N.68°E., 42.9 ft., shows scar.

A 36" Cedar bears S.45°E., 3.3 ft., scribe visible.