

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100537

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7702)

-----  
Set a stone 14x10x5 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which

A Cedar 12" dia., bears S.51°E., 68½ lks. mkd. ¼ S BT.

A Fir 13" dia., bears S.54 3/4°W., 8 lks. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Pgs 7619-20)

-----  
The ¼ sec. cor. partially obliterated, bearing trees overgrown. I reestablish the cor. in its original position for sec. 12 T31S R3W only, as follows:

Set a basalt stone 14x10x8 ins., 9½" in the ground for ¼ sec. cor. on East bd. Sec. 12, marked ¼ on W. face, from which

A Fir 18" dia., bears N.58°W., 50 lks. dist. mkd. ¼ S12 BT.

A Fir 15" dia., bears S.55°W., 8 lks. dist. mkd. ¼ S12 BT

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley; R.G. Boyd - Nov. 23, 1959 - C.S. 42/392-47

-----  
Determined by O.B.T:

28" Fir S.63°W., 5.3 ft.

At corner point, found stone and SET 1/2" x 40" Iron pipe, from which

8" Hemlock S.10°W., 10.0 ft. ¼ S12 BT.

6" Hemlock S.33°E., 22.6 ft. ¼ S12 BT.

8" Hemlock N.74°E., 16.8 ft. ¼ S12 BT.

6" Fir N.62°E., 7.6 ft. ¼ S12 X BT.

Survey by Loyd R. Moffit, L.S. #944 - For: Umpqua National Forest - Aug. 1978 - M 72-76

-----  
Found 1/2" pipe with stone scribed ¼, laying beside it.

Set 2" Pipe with 3" brass cap stamped "T31S R3W R2W 1/4 S12 PLS 944 1978"., from which

10" Hemlock bears N.74°E., 16.4 ft. scribe visible.

30" Cedar bears S.48°E. (Rec. S.51°E) 54.21 ft., bark scribe visible.

10" Fir bears S.54°W., 25.8 ft. scribed ¼ S12 BT.

DCSO-GIS Corner visitation - 2/23/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

-----  
Monument - 2" IP/BC Comment - OK

Cont.

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100537

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T31-3

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ron Quimby - Crew: N. Fromdahl & R. Olson - 9/2015 - C.S.  
File 65/89-25

-----  
Found - 3" brass cap (properly mkd)  
          11" hemlock N.74°E., 16.4 ft. good scar.  
          42" cedar S.48°E., 54.2 ft. good scar.  
          27" fir S.54°W., 25.8 ft. good scar.  
New - 9" fir N.76°W., 25.1 ft. scribed ¼ S12 BT  
Note - Area badly burnt 8/2015.  
          Hand held Lat & Long:  
              N 42°53.617'   W 122°59.59.618'  
          Compass decl. 15½°E.