

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100577

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 1 & 12 only, T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7702-03)

Set a stone 10x10x6 ins., 7" in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on N. and 5 notches on S. edges; from which

- A Fir 12" dia., bears N.24½°E., 77 lks. dist. mkd. T31S R2W S6 BT.
- A Fir 8" dia., bears S.16½°E., 111 lks. dist. mkd. T31S R2W S7 BT.
- A Laurel 17" dia., bears S.11½°W., 38 lks. dist. mkd. T31S R3W S12 BT.
- A Fir 15" dia., bears N.32½°W., 57 lks. dist. mkd. T31S R3W S1 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #766, dted May 10, 1906 - (DCSO records Vol. 18 Page(s) 7666)

Found iron stone 4x10x6 ins., above ground, firmly set marked and witnessed as described by the Surveyor General. Destroy marks on bearing trees referring to secs. 6 and 7.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - July 28, 1959 - C.S. File 42/392-23

Determined by O.B.T.s:
30" Fir N.24°E., 50.8 ft.
28" Fir S.16°E., 76.0 ft.
30" Laurel S.11°W., 25.0 ft., I rescribed S12 T31S R3W BT.
At corner point found stone and SET Iron pipe, from which
6" Hemlock bears S.33°W., 8.5 ft. mkd. S12 BT.
9" Chinquapin bears N.55°W., 15.6 ft. mkd. S1 R3W BT.
7" Chinquapin bears N.66°E., 10.4 ft. mkd. S7 R2W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - March 25, 1970 - C.S. File 54/28-100

Found - No trace of iron pipe, falls in skid road.
Orig. 32" D.Fir N.24°E., 50.8 ft., shows good scar.
Orig. 29" D.Fir S.16°E., 76.0 ft., shows good scar.
Orig. 31" Laurel N.11°W., 25.0 ft., scribe visible.
7" Chinquapin now 10", N.66°E., 10.4 ft. scribe visible.
6" Hemlock now 8" S.33°W., 8.5 ft. scribe visible.
9" Chinquapin now 12", N.55°W., 15.6 ft. scribe visible.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 100577

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 1 & 12 only, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Set Brass cap at cor. mkd: County Surveyors Office</p> <table><tr><td>R</td><td>T 31 S</td><td>R</td></tr><tr><td>3</td><td>S 1</td><td>2</td></tr><tr><td>W</td><td>S 12</td><td>W</td></tr></table> <p>1970</p> <p>This cor. lies 215.2 ft. So. of closing cor. for secs. 6 & 7, T31-2</p>	R	T 31 S	R	3	S 1	2	W	S 12	W
R	T 31 S	R							
3	S 1	2							
W	S 12	W							
<p>Ron Quimby - For: Roseburg Resources Co - Dec. 2014 - M166-27</p> <p>-----</p> <p>Found - Brass cap per 1970 DCSO renewal 15" Hemlock S.33°W., 8.5' healed face 9' Tall -11" Chinquapin snag N.55°W., 15.6' scribe visible 12" Chinquapin N.66°E., 10.4' healed face 35" Fir N.24°E., 50.8' healed face 31" Fir S.16°E., 76.0' healed face</p>									
<p>James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I</p> <p>-----</p> <p>Found - 2½" brass cap (properly mkd) 35" D.Fir with healed face set tag dated 10/13 N.24°E., 50.5' 13" chinquapin with healed face and tags dated 3/70 & 12/79 N.67°E., 10.4' 26.5" madrone with tag dated 12/79 S.13°W., 25.2' 17" hemlock with healed face and tags dated 12/79 & 3/70 S.34½°W., 8.5' 12" chinquapin snag with visible scribe and tags dated 1959 & 12/79 N.54°W., 16.0'.</p>									
<p> </p>									