

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7637)

Set a granite stone 15x8x6 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Cedar 6" dia., bears N.70°W., 30 lks. dist. mkd. ¼ S30 BT.
A Hemlock 12" dia., bears S.37°W., 43 lks. dist. mkd. ¼ S31 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 1966 - C.S. File 54/28-92

Found - No trace of stone.
6" Cedar, now down, N.70°W., 19.8 ft. mkd. "¼ S30 BT" visible.
12" Hemlock now 18", S.37°W., 28.4 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ $\frac{S \ 30}{S \ 31}$
1966

New BT - 11" D.Fir N.63°E., 29.0 ft. mkd. ¼ S30 CS BT.
This corner lies on steep bank 13.0 ft. North of creek.