

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7652)

Set a granite stone 15x8x8 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Fir 36" dia., bears N.62½°W., 29 lks. dist. mkd. ¼ S19 BT.

A Hemlock 5" dia., bears S.7½°W., 23 lks. dist. mkd. ¼ S30 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 1966 - C.S. File 54/28-95

Found - 15x8x8 stone, "¼" on N. face.
36" D.Fir, now snag, N.62½°W., 19.1 ft., scribe visible "S19".

5" Hemlock, now dead, S.7½°W., 15.2 ft., badly rotten face.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W

¼ $\frac{S \ 19}{S \ 30}$
1966

New BTs- 9" W.Fir S.18°E., 12.2 ft. mkd. ¼ S30 CS BT.

9" W.Fir N.60°E., 13.4 ft. mkd. ¼ S19 CS BT.

Corner lies 16.0 ft. West of ravine.