

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7657)

Set a granite stone 15x10x4 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 40" dia., bears N.70°W., 38 lks. dist. mkd. ¼ S18 BT.
A Fir 18" dia., bears S.41½°W., 20 lks. dist. mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 1966 - C.S. File 54/28-93

Found - 40" Fir, now down, N.70°W., 25.1 ft.
18" now 33" Fir, S.41½°W., 13.2 ft., shows good scr
15x10x4 stone mkd. "¼" on N. face at ¼ corner.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 18
S 19
1966
New BT - 15" D.Fir N.2½°W., 32.7 ft. mkd. ¼ S18 CS BT.
This corner lies 25.0 ft. West of ravine.