

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 177700

PRIMARY CORNER DESCRIPTION Sec. Cor. 31 & 32 only, So. bdy, T30-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May. 10, 1906 - (DCSO records Vol. 18 Page(s) 7668½)

Set a quartz stone 18 x 10 x 9 ins., 12" in the ground for cor. of secs. 31 and 32, T30S R2W, marked with 5 notches on E. and 1 notch on W. edge; from which
A Fir 40" dia., bears N.23°E., 189 lks. dist. mkd. T30S R2W S32 BT.
A Madrone 10" dia., bears N.47½°W., 53 lks. dist. mkd. T30S R2W S31 BT.

Survey by Loyd R. Moffit - For: U.S. Forest Service - Aug. 1978 - C.S. File 58/176-001C

Found - A stone 18 x 10 x 9 ins., marking the sec. corner.
A 36" Fir bears N.23°E., 124.7 ft., scar visible.
Set a 2" pipe with 3" brass cap stamped "T30S R2W S31 S32 T31S R2W S6 PLS 944 1978".
New BT - 8" Fir bears N.20°W., 15.4 ft. scribed T30S R2W S31 BT.
The original corner stone is buried along side the 2" pipe.
The new BT has a brass tag #944 nailed at BT scribe.

Fd. OK, July 1995 by B. Shaner - C.S. File 63/161-36A and M 119-64

Ron Quimby - For: Roseburg Resources Co. - Dec 2014 - M166-27

Found- Brass cap per 1978 U.S.F.S. renewal.
45" Fir N.23°E., 124.7' healed face
10" Fir N.20°W., 15.4' healed face
New BOs- 6" Fir N.33°W., 33.3' scribed "T30S R2W S31 BT"
5" FIR N.75°E., 28.8' scribed "T30S R2W S32 BT"