

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7636)

Set a granite stone 18x10x10 ins., 12" in the ground for cor. of secs. 29, 30, 31 and 32 marked with one notch on S. and 5 notches on E. edge, from which

- A Fir 9" dia., bears N.42°E., 26 lks. dist. mkd. T31S R2W S29 BT.
- A Fir 36" dia., bears S.9°E., 40 lks. dist. mkd. T31S R2W S32 BT.
- A Fir 7" dia., bears S.74¼°W., 43 lks. dist. mkd. t31S R2W S31 BT.
- A Fir 7" dia., bears N.41°W., 3 lks. dist. mkd. T31S R2W S30 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 -C.S. File 54/28-109A

Looked for, Not found.