

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7650-51)

A Madrone 15" dia., for cor. of secs. 19, 20, 29 and 30, I mark T31S S20 on NE.; R2W S29 on SE.; S30 on SW.; and S19 on NW. side, with 2 notches on S. and 5 notches on E. side, from which

A Fir 9" dia., bears N.32½°E., 51 lks. dist. mkd. T31S R2W S20 BT.

A Madrone 18" dia., bears S.70°E., 24 lks. dist. mkd. T31S R2W S29 BT.

A Fir 20" dia., bears S.14°W., 26 lks. dist. mkd. T31S R2W S30 BT.

A Fir 7" dia., bears N.36°W., 21 lks. dist. mkd. T31S R2W S19 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28 (Record source for this information not located, but other corners in this area were in this CS File-symbol for searched cor. on former renewal counter page)

Looked for, Not found.