

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7658)

Set a serpentine stone 12x10x8 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Cedar 15" dia., bears N.11°E., 43 lks. dist. mkd. ¼ S17 BT.
A Cedar 24" dia., bears S.41½°W., 27 lks. dist. mkd. ¼ S18 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 1966 - C.S. File 54/28-91

Found - Stone at ¼ corner with faint "¼" on W. face.
15" Cedar now 32", N.11°E., 28.3 ft., shows good scar.
24" now 33" Cedar, S.41½°W., 17.8 ft., opened for scribe "T".
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S18|S17
1966
New BT - 7" Laurel N.37°W., 11.8 ft. mkd. ¼ S18 CS BT.