

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7658)

-----  
Set a serpentine stone 15x8x6 ins., 10" in the ground for cor. of secs. 7, 8, 17 and 18, marked with 4 notches on S. and 5 notches on E. edge, from which  
A Fir 10" dia., bears N.50°E., 50 lks. dist. mkd. T31S R2W S8 BT.  
A Madrone 12" dia., bears S.38°E., 46 lks. dist. mkd. T31S R2W S17 BT.  
A Madrone 15" dia., bears S.48°W., 36 lks. dist. mkd. T31S R2W S18 BT.  
A Fir 9" dia., bears N.60°W., 45 lks. dist. mkd. T31S R2W S7 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 8, 1966 - C.S. File 54/28-90

-----  
Found - Stone at section corner, no marks.  
9" D.Fir now 17", N.60°W., 29.7 ft., shows scar.  
12" Laurel now 15", S.38°E., 30.4 ft., tree with rotten face.  
9" Fir, now burnt stump, N.50°E., 33.0 ft.  
15" Laurel now 19", S.48°W., 23.8 ft. opened for scribe.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 2 W  
S 7 | S 8  
S 18 | S 17  
1966

New BTs- 6" D.Fir N.20°E., 7.4 ft. mkd. T31S R2W S8 CS BT  
7" D.Fir S.49°E., 19.0 ft. mkd. T31S R2W S18 CSBT  
Reblazed and rescribed:  
19" Laurel S.48°W., 23.8 ft. mkd. T31S R2W S18 CS BT  
Yellow location tag on top of ridge about 370 ft. South of corner.