

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T30-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May. 10, 1906 - (DCSO records Vol. 18 Page(s) 7668½)

No stones available. Set a Cedar post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., marked ¼ S32 on N. face, from which
A Madrone 12" dia., bears N.65°E., 68 lks. dist. mkd. ¼ S32 BT.
A Cedar 8" dia., bears N.60°W., 13 lks. dist. mkd. ¼ S32 BT.

A.R. Evans, Deputy Co. Surveyor - April 1951 - C.S. File 44/121 and RM 1-30

Found - Orig. 8" Cedar N.60°W., 13 lks., down.
Orig. 12" Laurel N.65°E., 68 lks.
Set 4" x 4" x 42" Cedar stake for cor. 24" in ground marked N. side ¼S32.
Blaze and scribe BTs:
16" Fir N.66°E., 46.1 ft. mkd. ¼ S32 CS BT.
18" Fir N.39°W., 16.4 ft. mkd. ¼ S32 CS BT.

Douglas Co. Surveyors Office - John M. Powell and crew - Sept. 1966 - C.S. File 54/28-69

Found - Scribed stake at ¼ cor. mkd. "¼S32 CS".
Orig. 12" Laurel now 18", N.65°E., 44.8 ft., shows scar.
Orig. 8" Cedar stump, N.60°W., 8.5 ft., scribe visible.
10" D.Fir N.37°W., 17.5 ft., scribe visible "4".
17" Cedar N.69½°E., 46.4 ft. scribe visible "¼ S32 CS BT".

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S
¼ S 32 R2W
T 31 S
1966

Do not mark new BTs, as all trees in good condition.

Fd. OK Feb. 1984 by Wm. Ruppert - M 96-39
Fd. OK, July 1995 by B. Shaner - C.S. 63/161-36A & M 119-64
Fd Ok by Ken Hoffine 7/1999 M 133-1