

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7659)

Point for $\frac{1}{4}$ sec. cor. falls on a serpentine rock in place, 8x60x15 ins. above ground on which I cut a cross (x) at exact cor. point, $\frac{1}{4}$ N. of cross, from which
A Fir 12" dia., bears N.79°E., 59 lks. dist. mkd. $\frac{1}{4}$ S8 BT
A Pine 12" dia., bears S.63°W., 95 lks. dist. mkd. $\frac{1}{4}$ S17 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-31

Found - 12" Pine now 31", S.63°W., 62.7 ft., opened for scribing "S".

No trace of NE. BT, nor stone.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W

$\frac{1}{4}$ $\frac{S \ 8}{S \ 17}$
1966

New BTs- 7" Cedar S.61 $\frac{1}{2}$ °W., 43.9 ft. mkd. $\frac{1}{4}$ S17 CS BT.

11" Cedar N.41 $\frac{1}{2}$ °W., 22.4 ft. mkd. $\frac{1}{4}$ S8 CS BT.

Corner lies in fill slope of old rock pit.