

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7664-65)

Set a serpentine stone 12x10x6 ins., 8" in the ground for 1/4 sec. cor. marked 1/4 on N. face, from which
A Live Oak 15" dia., bears N.44°W., 53 lks. dist. mkd. 1/4 S5 BT.
A Madrone 10" dia., bears S.32°E., 24 lks. dist. mkd. 1/4 S8 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 1966 - C.S. File 54/28-96

Found - 15" Live Oak, now stump, N.44°W., 34.9 ft., opened for scribe "S BT".
10" Laurel S.32°E., 15.8 ft. No trace of this tree.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
1/4 $\frac{S \ 5}{S \ 8}$
1966
New BTs- 19" Laurel N.63°W., 112.4 ft. mkd. 1/4 S5 CS BT.
18" D.Fir, stump 2 ft. high, South, 5.4 ft. mkd. 1/4 S8 CS BT.

Corner lies in cut unit about 350.0 ft. West of road and 100.0 ft. North of ravine. Yellow location tag on road.