

PRIMARY CORNER DESCRIPTION Sec. cor. for 32 & 33 only (So.)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7611)

Set a washed stone 24x8x8 ins., 18" in the ground for cor. secs. 32 and 33 marked with 4 notches on E. and 2 notches on W. edges, from which
A Fir 24" dia., bears N.55°E., 67 lks. dist., mkd. T31S R2W S33 BT.
A Maple 12" dia., bears N.33½°W., 51 lks. dist. mkd. T31S R2W S32 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7617 and 7627 and 7645)

(Page 7617)
The cor. of secs.32 and 33, which is a washed stone 6x8x8 ins. above ground firmly set, mkd. and witnessed as described by the surveyor general.
(Page 7627)
The old cor. of secs. 32 and 33
I destroy the cor. and marks on bearing trees.
(Page 7645)
Intersect So. bdy. of the Township, 35.04 chs. N.89°49'E., of the closing cor. of secs. 5 & 6, T32-2. Set a slate stone 15x12x6 ins., 10" in the ground for closing cor. of secs. 32 and 33 marked CC on N. with 4 grooves on E. and 2 grooves on W. face, from which
A Fir 15" dia., bears N.23°E., 50 lks. dist. mkd. T31S R2W S33 BT.
A Fir 15" dia., bears N.4°W., 115 lks. dist. mkd. T31S R2W S32 BT.

Cor. looked for not found. Record source for this info. not located. Visual symbol on former cor. renewal visual page. Probably DCSO during the 1960's.