

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7635)

Set a slate stone 16x12x3 ins., 11" in the ground for cor. of secs. 28, 29, 32 and 33 marked with one notch on S. and 4 notches on E. edge, from which
A Fir 12" dia., bears N.82½°E., 52 lks. dist. mkd. T31S R2W S28 BT.
A Fir 20" dia., bears S.18½°E., 40 lks. dist. mkd. T31S R2W S33 BT.
A Madrone 8" dia., bears S.76½°W., 14 lks. dist. mkd. T31S R2W S32 BT.
A Madrone 8" dia., bears N.22°W., 29 lks. dist. mkd. T31S R2W S29 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-80

Found - Slate stone at section corner.
12" now 15" Fir N.82°E., 34.3 ft., shows good scar.
20" now 27" Fir S.18°E., 26.4 ft., shows good scar.
8" now 13" Laurel N.22°W., 19.1 ft.
8" Laurel, now dead, S.76½°W., 9.2 ft., faint scribe visible, "2" "B", other marks not legible.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
S 29 | S 28
S 32 | S 33
1966

New BT - 7" D.Fir S.34°W., 30.5 ft. mkd. T31S R2W S32 CS BT.