

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7645)

-----  
Set a granite stone 12x8x6 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Madrone 30" dia., bears N.57½°E., 14 lks. dist. mkd. ¼ S28 BT.  
A Fir 10" dia., bears S.87°W., 14 lks. dist. mkd. ¼ S29 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-51

-----  
Found - No trace of corner stone.  
10" Fir now 12", S.87°W., 9.2 ft., opened for scribe "S29".  
30" Laurel, down, N.57½°E., 9.2 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 2 W  
¼ S 29 | S 28  
1966  
New BTs- 16" D.Fir N.86°W., 19.5 ft. mkd. ¼ S29 CS BT.  
26" D.Fir N.40°E., 21.4 ft. mkd. ¼ S28 CS BT.