

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20 & 29 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7646)

No stones obtainable.

Set a Hemlock post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 20 and 29 only, marked T31S S29 on SW.; R2W S20 on NW. face, with 4 notches on N. and 2 notches on S. edge, from which

A Fir 36" dia., bears S.17½°W., 115 lks. dist. mkd. T31S R2W S29 BT.

A Fir 40" dia., bears N.86°W., 41 lks. dist. mkd. T31S R2W S20 BT.

Douglas Co. Surveyors Office - Clell Goodwin; Gary Langlitz; Vic Cangie; Lenora Ladig, crew - July 2, 1934 - C.S. File 57/34-3

Found - Orig. 40" Fir now 48" stump, with open blaze and visible scribe "S20 BT".

Orig. SW. BT completely gone leaving only a hole where it stood.

Set a brass cap on a 1" I.P. stamped: Douglas Co. Surveyor

T31S R2W
S20 | S 28
S29 |
1975

From which

A 48" Fir stump, OBT, bears N.86°W., 27.1 ft.

A 14" Yew scribed "T31S R2W S29 CS BT" in a double blaze, bears S.8°W., 93.3 ft.

The sec. corner for 21 and 28 bears N.2°W., 108.6 ft. (Call, N.0°03'W., 108.2 ft.)