

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300302

PRIMARY CORNER DESCRIPTION C C for Secs. 21 and 28 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7647)

(At a point on E. bdy. Sec. 20, 1.64 chs. N.0°3'W., of the cor. of secs. 20 and 29)

No stones obtainable.

Set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 21 and 28, marked CC T31S R2W on E.; S21 on N.; S28 on S. face, with 4 grooves on N. and 2 grooves on S. face, from which

A Madrone 7" dia., bears N.3½°E., 30 lks. dist. mkd. T31S R2W S21 BT.

A Fir 36" dia., bears S.56°E., 38 lks. dist. mkd. T31S R2W S28 BT.

Douglas Co. Surveyors Office - Clell Goodwin; Gary Langlitz; Vic Cangie; Lenora Ladig, crew - July 2, 1975 - C.S. File 57/34-2

Found - Orig. 36" Fir now 42" stump, with opened blaze and scribed "25" visible.

Orig. 7" now 15" Madrone, alive and well healed.

Set Brass cap on 1" I.P. stamped: Douglas Co. Surveyor

T 31 S R 2 W
S 20 | S 21 CC
 | S 28
 1975

from which

A 42" Fir stump, OBT, bears N.3½°E., 19.8 ft.

A 8" Chinquapin scribed "T31S R2W S21 CC CS BT" in double blaze, bears N.88°E., 38.3 ft.

Sec. Corner for 20 and 29 bears S.2°E., 108.6 ft. (Call, S.0°03'E., 108.2 ft.)