

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300342

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 21 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7648)

-----

No stones obtainable.

Set a Hemlock post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on W. bdy. sec. 21 marked ¼ S21 on E. face, from which

A Fir 9" dia., bears N.38½°E., 18 lks. dist. mkd. ¼ S21 BT.

A Yew 8" dia., bears S.66°E., 63 lks. dist. mkd. ¼ S21 BT.

Douglas Co. Surveyors Office - L.E. Monrean; P. Earle; J. Cook, crew - Dec. 15, 1975 - C.S. File 57/39-34

-----

Found - A rotted Fir stump approx. 12" dia., bears N.38½°E., 11.9 ft. Stump has been opened and is scribed "¼ S21 BT"

Other BT and orig. corner monument, not found.

Original call to a creek, North 53.1 ft., course West, checks good.

Set Brass cap at West ¼ cor. mkd: County Surveyors Office  
T 31 S R 2 W

¼ S 21

1975

New Accessories:

Set spike in 36" dia., Fir stump, bears N.19½°E., 122.4 ft. Spike stamped "BO 1".

Set spike in 36" dia. Fir stump, bears N.19°W., 108.8 ft. Spike stamped "BO 2".

The East ¼ cor. of Sec. 20 bears S.2°E., 163.9 ft. (Rec. S.0°03'E., 144.9 ft.)