

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION C C for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7654-55)

At a point on West bdy. Sec. 21, 3.17 chs. S.0°3'E. of a point on the So. bdy. Sec. 16. No stone obtainable.

Set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing corner of secs. 17 and 20, marked S17 on N.; S20 on S.; and CC T31S R2W on W. face, with 3 grooves on N. and S. faces, from which

A Fir 36" dia., bears S.64°W., 59 lks. dist. mkd. T31S R2W S20 BT.

A Fir 5" dia., bears N.42½°W., 25 lks. dist. mkd. T31S R2W S17 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - June 1961 - C.S. File 52/81-3

Found - Fir now 40", S.64°W., 38.9 ft., opened old blaze and found good scribing.

Portion of rotted stump of 5" Fir, N.42½°W., 16.5 ft., no scribing found.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W
S 17 |
S 20 | S 21
1966

New BTs- 9" W.Fir N.33½°W., 18.1 ft. mkd. T31S R2W S17 CS BT

7" W.Fir S.79°W., 12.2 ft. mkd. T31S R2W S20 CS BT.

(Note: "Sec. 21" stamped on brass cap in Jan. 1975 by Glenn Baughman.)