

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION C C for secs. 8 and 17 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7659)

(At a point 320 lks. S. of cor. of secs. 8, 9, 16 and 17, West Bdy. Sec. 16) Set a slate stone 18x10x4 ins., 12" in the ground for closing cor. of secs. 8 and 17, marked CC on W. with 2 grooves on N. and 4 grooves on S. face, from which
A Fir 36" dia., bears S.52°W., 95 lks. dist. mkd. T31S R2W S17 BT.
A Fir 20" dia., bears N.79°W., 106 lks. dit. mkd. T31S R2W S8 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew 0 June 1961 - C.S. File 52/81-6

Found both BTs recorded by Mensch, each shows good scars, dist. check OK. SW BT should be S.59°W. not S.52°W. Brg. to NW. BT is OK. Corner stone not found.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
C.C. S 8 | 16
S 17 |
1961

New BTs- 16" R.Fir bears N.76°W., 72.7 ft. scribed S8 T31S R2W CS BT.
36" Cedar bears S.75°E., 6.6 ft. scribed CC S8 & 17 T31S R2W CS BT.