

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION C C for Secs. 5 & 8 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7665)

At a point on W. bdy. Sec. 9, 287 lks. South of cor. of secs. 4, 5, 8 and 9. Set a basalt stone 15x9x6 ins., 10" in the ground for closing cor. of secs. 5 and 8, marked CC on W. with 1 groove on N. and 5 grooves on S. face, from which
A W.Oak 7" dia., bears S.57 3/4°W., 298 lks. dist. mkd. T31S R2W S8 BT.
A B.Oak 7" dia., bears N.12½°W., 96 lks. dist. mkd. T31S R2W S5 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - June 1961 - C.S. File 52/81-5

Foun both BTs recorded by Mensch, show good scars. We do not open. Also find corner stone which shows notches. Set brass cap alongside corner stone mkd.
County Surveyors Office 1961
T 31 S R 2 W
S 5 | S 9
S 8 |
New BT - 22" Cedar bears S.64°W., 31.4 ft. scribed S8 T31S R2W CS BT.

DCSO-GIS Corner visitation - 7/7/2004 - Typed: 2/9/2011 - C.S. File 67/33-1

Monument - nothing listed
Comment - nothing listed