

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7608)

Set ¼ sec. post, from which
A Fir 15" dia., bears S.25°E., 30 lks.
A Laurel 15" dia., bears N.25°W., 84 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7683)

The ¼ sec. cor. nearly obliterated, the only remaining trace being one bearing tree. I reestablish the cor. in its original position as follows:
Set a basalt stone 15x10x5 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 18" dia., bears S.25°E., 31 lks. dist. mkd. ¼ S4 BT.
A Madrone 4" dia., bears N.3½°W., 85 lks. dist. mkd. ¼ S5 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-104

Found - 18" D.Fir now 25", S.25°E., 20.4 ft., tree had been opened, "BT S" visible.
No trace of 4" Laurel.
Stone with "¼" mark, out of ground.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 5 | S 4
1966
New BT - 8" D.Fir S.22°W., 10.6 ft. mkd. ¼ S5 CS BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Feb. 27, 1970 - C.S. File 54/28-105

Found 1966 DCSO brass cap. I now destroy everything that refers to sec. 5, so it now reads: County Surveyors Office
T 31 S R 2 W
¼ | S 4
1966
Old BT - 18" D.Fir now 25", S.25°E., 20.4 ft., tree had been opened and shows scribe "S4 BT"
New BT - 6" D.Fir N.83½°E., 13.6 ft. mkd. ¼ S4 CS BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 300643

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by William Ruppert - For: U.S. Forest Service - Feb. 1979 - C.S. File 58/176-22

Found - 1" Iron pipe on 2½" brass cap, properly mkd. Stone
 alongside pipe.
 8" D.Fir N.85½°E., 13.6 ft., good scar.
 28" D.Fir, uproot, S.28°E., 21.4 ft.
 12" D.Fir S.16 ¾°W., 10.5 ft., good scar.
Scribed- "¼ S4 BT" on 14" D.Fir, bears N.29 ¾°E., 27.0 ft.
 Attached ¾" brass washer "LS 866" to lower
 blaze.

BLM dependent resurvey by Timothy J. Moore, Cadastral
Surveyor and Robert H. Browning, Surveying Technician, under
Group No. 2071, surveyed April/May 2004 - (DCSO records Vol.
55 Page(s) 21384-5)

The ¼ sec. cor. of sec. 4 only, perpetuated by Powell, in
1966 & again in 1970, further perpetuated by Ruppert, in 1979
monumented with an iron pipe, 1¼" dia. firmly set, projecting
12" above the ground, with brass cap (properly) mkd.
from which the remains of an original BT reported by Mensch
A roothole bears S.25°E., 20.5 ft., alongside of which is
the displaced sawed fir stump, 27" dia., with a healed
double blaze.
and the bearing trees mkd. by Powell
A fir, 11" dia., bears N.87½°E., 13.5 ft., with a healed
double blaze.
A fir, 16" dia., bears S.23¼°W., 10.7 ft., with a healed
double blaze.
and a bearing tree mkd. by Ruppert
A fir, 21" dia., bears N.31½°E., 26.2 ft., with a healed
double blaze.