

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 21 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7605)

Set ¼ sec. post, from which
A Fir 24" dia., bears N.10°E., 18 lks.
A Fir 10" dia., bears S.40°W., 18 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7675)

The ¼ sec. cor., nearly obliterated. The only remaining evidence is one bearing tree, badly defaced by fire. I reestablish the cor. in its original position as follows:
Set a basalt stone 14x10x8 ins., 9½" in the ground marked ¼ on N. face, from which
A Fir 18" dia., bears N.65°E., 72 lks. dist. mkd. ¼ S21 BT
A Cedar 40" dia., bears S.42°E., 31 lks. dist. mkd. ¼ S28 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-102

Found - Stone mkd. ¼ on North face.
18" Fir, now stump, N.65°E., 47.5 ft., opened for scribe "BT".
40" Cedar now 43", S.42°E., 20.5 ft., had been opened and face burnt.
1" Iron pipe found also. (No record)

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W
¼ S 21
S 28
1966

New BTs- 9" W.Fir S.17°W., 17.6 ft. mkd. ¼ S28 CS BT.

6" W.Fir N.88°W., 12.1 ft. mkd. ¼

1" Iron pipe 1.4 ft. West of brass cap.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - March 16, 1970 - C.S. File 54/28103

Found - 1966 Co. surveyors brass cap.
9" W.Fir S.17°W., 17.6 ft. mkd. ¼ S28 CS BT.
6" W.Fir N.88°W., 12.1 ft. mkd. ¼ S21 CS BT.

I now destroy everything that refers to Sec. 28, so it now reads:
(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 21 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

County Surveyors Office
T 31 S R 2 W
¼ S 21
1966

New BT - 10" Hemlock N.55°E., 61.7 ft. scribed ¼ S21 CS BT
Destroyed scribing on 9" Fir S.17°W., 17.6 ft.