

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7605)

Set ¼ sec. post, from which
 An Oak 18" dia., bears S.40°W., 45 lks.
 An Oak 12" dia., bears N.60°W., 8 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7675-76)

The ¼ sec. cor. nearly obliterated. No trace is found of the post and the bearing trees are deeply overgrown. I re-establish the cor. in its original position as follows:
Set a slate stone 14x8x6 ins., 9½" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
 A B.Oak 14" dia., bears N.60°W., 9 lks. dist. mkd. ¼ S16 BT.
 A B.Oak 30" dia., bears S.40°W., 47 lks. dist. mkd. ¼ S21 BT.

Looked for, not found, Aug. 1966 by DCSO - J.Powell - C.S. File 54/28-102A & 54/28-109A

Survey by Glenn Baughman - For: U.S. Forest Service - Jan. 1975 - C.S. File 58/33 and M 56-7

Set 2" Iron pipe with 3" brass cap stamped "T31S R2W 1/4 16 21 1975 OLS 536", from which bears
 A 13" Pine N.22°W., 47.5 ft. scribed ¼ S16 BT.
 A 10" Pine S.59°W., 36.2 ft. scribed ¼ S21 BT.