

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7607)</p> <p>-----</p> <p>Set ¼ sec. post, from which An Oak 12" dia., bears N.87½°E., 123 lks. An Oak 10" dia., bears S.83°E., 28 lks.</p>
<p>GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7684)</p> <p>-----</p> <p>The ¼ sec. cor. which is a post greatly decayed with bearing trees deeply overgrown. I reestablish the cor. in its original position as follows: Set a basalt stone 12x10x6 ins., in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which A W.Oak 24" dia., bears N.70°E., 8 lks. mkd. ¼ S4 BT. A W.Oak 12" dia., bears S.83°E., 28 lks. dist. mkd. ¼ S9 BT.</p>
<p>Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - July 15, 1976 - M 56-49</p> <p>-----</p> <p>Set 5/8" x 54" Iron rod and alum. cap, from which 10" Cedar S.37°W., 8.2 ft. 12" Cedar N.40°E., 23.3 ft.</p>
<p>BLM dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group No. 2071, surveyed April/May 2004 - (DCSO records Vol. 55 Page(s) 21382-3)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 4 & 9, monumented with the basalt stone set by Mensch, 12x10x6", firmly set, projecting 3" above the ground, mkd. ¼ on the N face, from which the remains of the original bearing trees A roothole, bears S. 88° E., 73.9 ft., the displaced sawed and burnt stump, with the bottom of a healed blaze, with no marks visible. (Record, N.87½°E., 81.2 ft.) and an the remains of an original BT reported by Mensch A roothole, bears S.82°E., 23.0 ft., with no remains of the trunk. (Record, S.83°E., 18.5 ft.) and a bearing tree mkd. by Mensch An oak, 30" dia., bears N.70° E., 64.7 ft. with no marks visible on an opened blaze. A roothole, bears S.82°E., 23.0 ft., with no remains of the trunk. (Record, S.83°E., 18.5 ft.) cont. next pg</p>

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a bearing tree mkd. by Mensch
An oak, 30" dia., bears N.70°E., 64.7 ft., with no marks visible on an opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T31S R2W
¼ S 4
S 9

2004

from which a new bearing tree

A cedar, 12" dia., bears S. 45¼°E., 6.2 ft., mkd. ¼ S9 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the basalt stone inverted alongside the stainless steel post.

From this corner, a point reestablished as the ¼ sec. cor. of secs. 4 & 9 by Johnstone, in 1979, bears N.74°36'09"W., 9.13 ft. The Mensch corner monument (original position) was not recovered, therefore, this point is not accepted or utilized during the course of this survey, monumented with an iron rod, 5/8" diam., firmly set, projecting 6" above the ground, with aluminum cap, 1" dia., affixed to top, mkd. ¼, from which the remains of BTs mkd. by Johnstone

A sawed cedar stump, 24" dia., bears N.41½°E., 23.2 ft., with a healed blaze.

A sawed cedar stump, 19" dia., bears S.37¾°W., 8.0 ft., with a healed blaze.

