

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - July 15, 1976 - M 56-49

Set 5/8" x 30" Iron rod and alum. cap, from which
38" Pine, N.11½°W., 223.6 ft.
Rock mound, S.38½°W., 25.5 ft.
Pickett Butte L.O., N.62½°E.
Diamond Rock, S.14½°E.

BLM dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group No. 2071, surveyed April/May 2004 - (DCSO records Vol. 55 Page(s) 21385-6)

The center ¼ sec. cor. of sec. 4, established by Johnstone, in 1976,, and is accepted as the cor., monumented with an iron rod, ¾" dia., firmly set, projecting 6" from the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap, 1" dia., affixed to top, mkd. ¼, from which the remains of a bearing tree and accessories reported by Johnstone
Pickett Butte Lookout, bears N.64°15'21"E.
Diamond Rock, bears S.13°07'39"E.
A mound of stone, 3 ft. base, 1½ ft. high, bears S.39¾°W., 25.9 ft.
A sawed pine stump, 36" dia., bears N.14¼°W., 223.9 ft. with no marks visible.

Add marks on the cap to now read
T31S R2W
C 1/4
S 4
2004

Latitude: 42°54'33.617"N.
Longitude: 122°57'09.079 W
NAD 1983 (CORS 96)