

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 27, 28, 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7633-34)

A White Fir 14" dia. for cor. of secs. 27, 28, 33 and 34, I mark T31S R2W on NE.; R2W S34 on SE.; S33 on SW.; and S28 on NW. side, with 1 notch on S. and 3 notches on E. sides, from which

A Fir 14" dia., bears N.40°E., 34 lks. dist. mkd. T31S R2W S27 BT.

A Fir 7" dia., bears S.50°E., 54 lks. dist. mkd. T31S R2W S34 BT.

A Madrone 12" dia., bears S.85°W., 50 lks. dist. mkd. T31S R2W S33 BT.

A Fir 12" dia., bears N.68°W., 63 lks. dist. mkd. T31S R2W S28 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-79

Found - 14" now 21" W.Fir Corner tree.
14" now 18" W.Fir N.40°E., 22.4 ft., shows good scar.
12" now 27" W.Fir N.68°W., 41.6 ft., shows good scar.
7" now 13" D.Fir S.50°E., 35.6 ft., opened for scribing "B".
No trace of SW. BT.

Set Brass cap at cor. on West side of corner tree mkd:

County Surveyors Office

T 31 S R 2 W

S 28 | S 27

S 33 | S 34

1966

New BT - 14" W.Fir S.31°W., 31.0 ft. mkd. T31S R2W S33 CS BT